



# COLOR EXPRESS 10S - C512iX PLUS



SOLVENT SERIES

## REALISTIC IMAGE



## MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry

JAPAN  
KONICA  
Print Head



SOLVENT SERIES

◀ COLOR EXPRESS 10S - C512iX

HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)

# COLOR EXPRESS 10S - C512iX PLUS

▶ Professional Inkjet Printer



## TECHNICAL SPECIFICATIONS

Dimension	4500mm(L) x 940mm(W) x 1430mm(H)									
Weight	800kg									
Max. Print Width	3200mm									
Max. Media Width	3340mm									
Ink Type	Solvent Based Pigment Ink									
Ink Color										
Ink Supply System	Negative Pressure Recirculation System									
Print Head	KONICA 512i (30pl), Optional: KONICA 1024i (13pl)									
No. of Print Head	4 / 8units									
Print Resolution	480x540dpi, 480x720dpi, 480x1080dpi									
Printing Speed	<table><tr><td>Production Mode</td><td>105 m<sup>2</sup>/h</td><td>210 m<sup>2</sup>/h</td></tr><tr><td>Quality Mode</td><td>70 m<sup>2</sup>/h</td><td>140 m<sup>2</sup>/h</td></tr><tr><td>High Precision Mode</td><td>52 m<sup>2</sup>/h</td><td>105 m<sup>2</sup>/h</td></tr></table> <small>A Printhead B Printhead</small>	Production Mode	105 m <sup>2</sup> /h	210 m <sup>2</sup> /h	Quality Mode	70 m <sup>2</sup> /h	140 m <sup>2</sup> /h	High Precision Mode	52 m <sup>2</sup> /h	105 m <sup>2</sup> /h
Production Mode	105 m <sup>2</sup> /h	210 m <sup>2</sup> /h								
Quality Mode	70 m <sup>2</sup> /h	140 m <sup>2</sup> /h								
High Precision Mode	52 m <sup>2</sup> /h	105 m <sup>2</sup> /h								
Print Mode	Uni- and Bi- Direction									
Media Type	Banner Flex, Canvas, Mesh Paper, Synthetic Paper,PVC, Reflective Film, Sticker, Tarpaulin, Textile, Wallcoverings, etc.									
RIP & Control Software	Hapond Printer Manager, PhotoPrint									
Cleaning System	Positive Flush									
Drying System	Infrared Heating with Fan Drying System									
Media Handling	Auto Media Release / Take Up System									
Image Format	BMP, TIFF, JPEG, EPS, PDF, etc.									
Color Management	ICC Profile									
Data Interface	USB 2.0 / 3.0									
Input Voltage	Single Phase, AC 220V±10%, 50/60Hz									
Working Environment	Temperature : 20°C ~ 28°C Humidity : 40%~70%									

Technical specifications are subject to change without prior notice.



HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)



+603-4296 3733



3-4296 9733



sales@hapond.com.my



hapond.com.my



facebook.com/haponddigital



No. 21, Jalan Merdeka Ria 1,  
Merdeka Ria Industrial Park, 68000 Ampang,  
Selangor, Malaysia.

