



TH60F3 UV

UV DTF PRINTER SERIES



MAIN APPLICATION


Decoration Industry

Advertising Industry

Packaging Industry

Gift Industry


PRODUCT DETAILS




Auto Powder System



Air Purifier System



Gold Foil Spot Channel



Stitching Effect

TH60F3 UV



TECHNICAL SPECIFICATIONS

MODEL	TH60F3 UV	
Model	TU60F3-UV-TH DTF Printer	
Printerhead and Quantity	3 Unit EPSON 1600	/ EPSON i3200
Printing resolution	2400DPI	
Printing speed	6PASS 5m ² /h, 10PASS 4m ² /h / 6PASS 8m ² /h, 10PASS 6m ² /h	
Printing width	600mm	
Printing medium	Release paper, release film, AB film	
Ink	UV ink capacity: 1.8L with liquid level alarm	
Color	CMYK + White	
RIP Software	Photoprint	
Operarting system	Windows 10 or above	
Picture format	Tiff, Jpeg, Bitmap, Eps, Pdf, PNG	
Operation enviroment	The temperature is 25°C-30°C, and the humidity is 50%-75%	
Power	50HZ/60HZ/220V, power 2050W	
Interface	Gigabit network card	
Mechine size	1550*1310*1000mm (length x width x height)	
Packaging size	2350*1050*1150mm (lenght x width x height)	
Gross weight	160/195KG	
Net weight	288/362.5KG	

Technical specifications are subject to change without prior notice.

