



UV INKJET PRINTER (FLATBED) H6090EI / H0906EI

UV INKJET SERIES



MAIN APPLICATION

- ✓ Decoration Industry
- ✓ Advertising Industry
- ✓ Interior Design Industry
- ✓ Packaging Industry
- ✓ Exhibition Industry
- ✓ Leather & Textile Industry




EPSON i3200 U1




Unique Designed
Compacted Body




Laser Media Detector



Constant Temperature
Printhead Heater



White Ink
Recirculation System



Enhanced Aluminium
Structure



Cylinder Printing Kit
(Optional)



Camera Positioning System
(Optional)

APPLICATION



UV INKJET PRINTER (FLATBED) H6090EI / H0906EI



TECHNICAL SPECIFICATIONS

Model	H6090EI	H0906EI
Dimension (LxWxH mm)	1528x1634x1368	2180x1565x1371
Weight (kg)	374	492
Max. Print Size (mm)	600x900	900~600
Max. Media Thickness	Up to 180mm	Up To 150mm
Printing Speed	CMYK+W+V	CMYK+W CMYK+W+V
Draft 720x1200dpi	Weak 2.9mins/sheet	Weak 4.2mins/sheet 4.5mins/sheet
Production 720x1200dpi	Normal 3.7mins/sheet	Medium 5.0mins/sheet 5.5mins/sheet
Hi-Res 720x1800dpi	Normal 4.4mins/sheet	Week 6.3mins/sheet 6.8mins/sheet
Photo 720x1800dpi	Strong 5.6mins/sheet	Medium 7.5mins/sheet 8.3mins/sheet
Ink Cofiguration	KCMY; W+KCMY; W+KCMY+V	CMYK; CMYK+W; CMYK+W+V
Print Head	EPSON i3200 U1	
No. Of Print Head	3 Units	2~3 Units
Curring System	3x Air cooling LED UV curing lamps	4 Water cooling LED UV curing lamps
Printing Technolgy	Drop-On-Demand Piezo with Variable Dot	
Resolution	720x1200dpi, 720x1800dpi	
Media Type	Acrylic, Aluminum Sheet, Form Board, PVC Board, Leather, Glass Bottle, Wood, Ceramic, tiles, etc	
Ink Supply System	Bulk Ink Supply System with White INk Reciculation System	
Software	FlexiPRINT MiniUV+GZ Control Console	
Data Interface	Gigabit Port	
Input Voltage	Single Phase, AC220V $\pm$, 50/60Hz, 10A	
Working Enviroment	Temperature: 20°C - 28°C	Humidity: 40%-60%RH

Technical specifications are subject to change without prior notice.

