



Hapond 1604SM/2104SM /3204SM

ALL IN ONE DYE SUBLIMATION DOUBLE SIDE PRINTER

SUBLIMATION SERIES

INSPIRING INNOVATION



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry


Packaging Industry

Exhibition Industry

Leather & Textile Industry



SMART HEATING
CONTROL



MAGNETIC ENCODER
SENSOR



ADJUSTABLE PRINT
PLATTEN



HIGH-STRENGTH SPECIAL
STEEL

SUBLIMATION SERIES

▶ Hapond 1604SM/2104SM
/3204SM

Hapond 1604SM/2104SM /3204SM

ALL IN ONE DYE SUBLIMATION DOUBLE SIDE PRINTER



TECHNICAL SPECIFICATIONS

Model	1604SM	2104SM	3204SM
Dimension (LxWxH mm)	3664x1697x1998	4164x1697x1998	5289x1854x2217
Weight (kg)	2000	2000	3000
Max. Print Size (mm)	1600	2100	3200
Max. Media Size (mm)	1600	2100	3200
Printing Speed			
3PASS 360x1800dpi	85 sqm/h	95 sqm/h	140 sqm/h
4PASS 720x1200dpi	65 sqm/h	75 sqm/h	120 sqm/h
Ink	C M Y K		
Print Head	EPSON i3200 A1		
No. Of Print Head	8 Units (4+4)		
Ink Type	Water-based sublimation		
Printing Mode	Uni and Bi - Direction		
Resolution	360x1800dpi, 720x1200dpi		
Media Type	Retro-style banner, curtains, tension fabric backdrop, flags, giant wind flag, beach flag light box and etc		
Fixation	Intergrated; Straight-through		
RIP Software	Photo print / Main top / RIIN		
Max Roll Weight	60kg		
Max Fixition Temperature	200°C		
Input Voltage	380V(fixation) 220V(printer) 50-60Hz		
Working Enviroment	Temperature: 20°C - 28°C		Humidity: 40%-60%RH

Technical specifications are subject to change without prior notice.



HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)



+603-4296 3733



+603-4296 9733



sales@hapond.com.my



hapond.com.my



facebook.com/haponddigital



21 - 23 Jalan Bukit Permai Utama 3,
Taman industri Bukit Permai,
56100 Cheras, WP Kuala Lumpur

