

INSPIRING INNOVATION

ES-R1625OD/OS/ODS



ES-R1625OD/OS/ODS-AT4



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry



FINAL PRODUCT



DIGITAL CUTTER SERIES

◀ **ES-R1625OD/OS/ODS-AT4**

DIGITAL CUTTING MACHINE

ES-R16250D/OS/ODS-AT4



TECHNICAL SPECIFICATIONS

Model	ES-R16250D	ES-R16250S	ES-R16250DS-AT4
Table Size	1620 X 2550 mm		
Working Size	1520 x 2500 x 50 mm		
Feed Height	100 mm		
Spindle	None	3KW/220V Water Cooling	5.5KW/220V Water Cooling ATC Spindle
Tool	Oscillating Knife & Drag Knife	Oscillating Knife & Spindle	Oscillating Knife & Drag Knife & Spindle
Oscillating Knife Frecuancy	15000~20000 rpm		
Shank Mode	None	By Manual	HSK
Tool Stock	None	ER20	HSK E32
Spindle Rotary Speed	None	0~40000 rpm	0~36000 rpm
Tool Diameter	None	Ø3.175, Ø4, Ø6, Ø8	Ø3.175, Ø4, Ø6, Ø8, Ø12.7
Driver	AC Servo		
Control System	SIGNKEY Customized Control System		
Transmission	Z-Ball Screw Direct Connection; X,Y Rack + Planetary Reducer		
XYZ Rail	Imported Linear Rail		
Max. Unloaded Speed	120m/minute		
Voltage	380V,50-60Hz		
Working Table	Vacuum & Rolling Feeding		
Sorting Platfrom	Optimal Sorting platform Includes Projector And Projector Stand		
Dust Collect	Powerfull Dust Collector		
Vacuum Pump	7.5KW Air Cooling		
Machine Dimension	3900 x 3000 x 1630 mm		3900/5300 (sorting platform) x 2500 x 1700 mm
N.W/G.W kg	1700/2000		2200/2500

Technical specifications are subject to change without prior notice.

