

REALISTIC IMAGE



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry

JAPAN
KONICA Print Head



SOLVENT SERIES

◀▶ **COLOR EXPRESS 10S - C512iX**

HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)

HAPOND SOLVENT PRINTER COLOR EXPRESS 10S - C512iX



TECHNICAL SPECIFICATIONS

Dimension	4500mm(L) x 940mm(W) x 1430mm(H)		
Weight	800kg		
Max. Print Width	3200mm		
Max. Media Width	3340mm		
Ink Type	Solvent Based Pigment Ink		
Ink Color			
Ink Supply System	Negative Pressure Recirculation System		
Print Head	KONICA 512i (30pl), Optional: KONICA 1024i (13pl)		
No. of Print Head	4 / 8units		
Print Resolution	480x540dpi, 480x720dpi, 480x1080dpi		
Printing Speed	Production Mode	105 m ² /h	210 m ² /h
	Quality Mode	70 m ² /h	140 m ² /h
	High Precision Mode	52 m ² /h	105 m ² /h
Print Mode	Uni and Bi-Direction		
Media Type	Banner Flex, Canvas, Mesh Paper, Synthetic Paper,PVC, Reflective Film, Sticker, Tarpaulin, Textile, Wallcoverings, etc.		
RIP & Control Software	Hapond Printer Manager, PhotoPrint		
Cleaning System	Positive Flush		
Drying System	Infrared Heating with Fan Drying System		
Media Handling	Auto Media Release / Take Up System		
Image Format	BMP, TIFF, JPEG, EPS, PDF, etc.		
Color Management	ICC Profile		
Data Interface	USB 2.0 / 3.0		
Input Voltage	Single Phase, AC 220V±10%, 13A, 50/60Hz		
Working Environment	Temperature	: 20°C ~ 28°C	
	Humidity	: 40%~70%	

Technical specifications are subject to change without prior notice.

