

REALISTIC IMAGE



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry

**JAPAN
DIMATIX (Fujifilm)
Print Head**



SOLVENT SERIES

◀ **COLOR EXPRESS GZH5306SG**

HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)

HAPOND SOLVENT PRINTER COLOR EXPRESS GZH5306SG



TECHNICAL SPECIFICATIONS

Dimension	7550 x 1800 x 1515 (LxWxH mm)		
Weight	2700kg		
Max. Print Width	5300mm		
Ink Type	Solvent Based		
Ink Color	C M Y K		
Ink Supply System	Negative Pressure Recirculation System		
Print Head	STARFIRE 1024 (25pl), Optional: STARFIRE 1024 (10pl)		
No. of Print Head	4 / 6 units		
Print Resolution	300x400dpi, 300x600dpi, 300x800dpi, 600x400dpi, 600x600dpi, 600x800dpi		
Printing Speed	Production Mode Quality Mode High Precision Mode	181 m ² /h 142 m ² /h 90 m ² /h	275 m ² /h 216 m ² /h 135 m ² /h
Print Mode	Uni and Bi-Direction		
Media Type	Banner Flex, Canvas, Mesh Paper, Synthetic Paper, PVC, Reflective Film, Sticker, Tarpaulin, Textile, Vinyl, Wallcoverings, etc		
RIP & Control Software	Hapond Printer Manager, PhotoPrint, Optional: Onyx RIP		
Drying System	Pre, mid & extended heater + IR Dryer		
Media Handling	Automatic media feeding and taking up system with pneumatic shaft		
Image Format	BMP, TIFF, JPEG, EPS, PDF, etc.		
Color Management	ICC Profile		
Data Interface	USB 2.0/3.0		
Input Voltage	50Hz/AC, 220V+-10%, 27A (Printer)+380V+10%, 27A(IR Dryer)		
Working Environment	Temperature : 20°C~28°C Humidity : 40%~70%		

Technical specifications are subject to change without prior notice.

