

REALISTIC IMAGE



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry

JAPAN
DIMATIX (Fujifilm)
Print Head



SOLVENT SERIES

◀ **COLOR EXPRESS HS 3202/04**

HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)

HAPOND SOLVENT PRINTER COLOR EXPRESS HS3202/04



TECHNICAL SPECIFICATIONS

Dimension	4800 x 960 x 1250 (LxWxH mm)				
Weight	1115kg				
Max. Print Width	3200mm				
Ink Type	Solvent Pigment Ink				
Ink Color					
Ink Supply System	Negative Pressure Recirculation System				
Print Head	STARFIRE 1024 (10pl), Optional: STARFIRE 1024 (25pl)				
No. of Print Head	2 / 4units				
Print Resolution	300x400dpi, 300x600dpi, 300x800dpi, 600x400dpi, 600x600dpi, 600x800dpi				
Printing Speed	Production Mode	70 m²/h	2 Printhead	140 m²/h	4 Printhead
	Production Mode	45 m²/h		90 m²/h	
	Quality Mode	35 m²/h		70 m²/h	
	High Presicion Mode	22 m²/h		44 m²/h	
Print Mode	Uni- and Bi- Direction				
Media Type	Banner Flex, Canvas, Mesh Paper, Synthetic Paper,PVC, Reflective Film, Sticker, Tarpaulin Textile, Vinyl, Wallcoverings, etc.				
RIP & Control Software	Hapond Printer Manager, PhotoPrint, Optional: Onyx RIP				
Drying System	Pre, mid, post & extended heater plus intelligen QT drying system				
Media Handling	Automatic media feeding and taking up system with pneumatic shaft				
Image Format	BMP, TIFF, JPEG, EPS, PDF, etc.				
Color Management	ICC Profile				
Data Interface	USB 2.0/3.0				
Input Voltage	50Hz / AC, 220+-10% 13A(Printer)+18Ax2(IR Drying System)				
Working Environment	Temperature : 20°C - 28°C Humidity : 40% - 70% RH				

Technical specifications are subject to change without prior notice.

