

BRILLIANT START



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry

Auto Height Detector



Superior Quality UV LED System



High Quality Cable Chain



Printhead RICOH G6 Print Head



UV FLATBED SERIES

◀ **H2513GN**

HAPOND UV FLATBED PRINTER

H2513GN



TECHNICAL SPECIFICATIONS

Dimension	4572 x 2179 x 1585 (LxWxH mm)		
Weight	1200kg		
Print/Media Width	2500x1300 (WxL mm)		
Media Thickness	Max. 100mm		
Ink Type	UV Curable Ink		
Ink Color	 Optional: Lc,Lm,Varnish		
Print Head	RICOH G6 (5pl)		
No. of Print Head	Max. 8 units		
Print Resolution	720x900dpi, 720x1200dpi		
Printing Speed	Production Mode	4 Print Head 33 m ² /h	6 Print Head 50 m ² /h
	Quality Mode	22 m ² /h	33 m ² /h
	High Precision Mode	16 m ² /h	25 m ² /h
Print Mode	Uni- and Bi- Direction		
Media Type	Acrylic, Aluminium, Ceramic Tiles, Corrugated Board, Foam Board, Glass, Metal Plate, Tarpaulin, Textile, Non-woven, Wallcoverings.		
RIP & Control Software	Hapond Printer Manager, Optional: Caldera, PhotoPrint		
Curing System	LED UV System		
Cleaning System	Positive Flush		
Image Format	BMP, TIFF, JPEG, EPS, PDF, etc.		
Color Management	ICC Profile		
Data Interface	USB 2.0/3.0		
Input Voltage	220~240VAC (50/60Hz), 32A		
Working Environment	Temperature : 20°C-28°C		Humidity: 40%-70%RH

Technical specifications are subject to change without prior notice.

HAPOND
DIGITAL TECHNOLOGY SDN BHD



+603-4296 3733



+603-4296 9733



sales@hapond.com.my



hapond.com.my



facebook.com/haponddigital



21-23 Jalan Bukit Permai Utama 3,
Taman Industri Bukit Permai,
56100 Cheras, Kuala Lumpur

