

BRILLIANT START



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry

Auto Height Detector



Superior Quality UV LED System



High Quality Cable Chain



Printhead RICOH G6 Print Head



UV INKJET SERIES

◀ **H3220GN**

HAPOND UV FLATBED PRINTER H3220GN



TECHNICAL SPECIFICATIONS

Model	H3220GN	
Dimension (LxWxH mm)	5400 x 3030 x 1500	
Weight (kg)	2100	
Max. Printing Width (mm)	3200 x 2000 (WxL)	
Max. Media Thickness (mm)	Max. 100	
Ink Color	 Optional: 	
Ink Type	UV Curable Ink	
Print Head	RICOH G6 (5PL)	
No. Of Print Head	Max. 8 Units	
Printing Resolution (dpi)	720x900, 720x1200	
Printing Speed (m ² /h)	4 Print Head	6 Print Head
Production Mode	37	58
Quality Mode	29	42
High Precision Mode	22	31
Printing Mode	Uni and Bi-Direction	
Media Type	Acrylic, Aluminum, Ceramic Tiles, Corrugated Board, Foam Board, Glass, Metal Plate, Back-Lit, Banner Flex, Canvas, Mesh Paper, Synthetic Paper, Reflective Film, Sticker, Tarpaulin, Textile, Non-Woven, Wall coverings, Soft Film, etc	
RIP & Control Software	Hapond Printer Manager, Optional: Caldera, PhotoPrint	
Curing System	LED UV System	
Cleaning System	Positive Flush	
Image Format	BMP, TIFF, JPEG, EPS, PDF, etc	
Color Management	ICC Profile	
Data Interface	USB 2.0/3.0	
Input Voltage	220~240VAC(50/60Hz), 32A	
Working Environment	Temperature: 20°C - 28°C	Humidity: 40%-70% RH

Technical specification are subject to change without prior notice.

