

BRILLIANT START



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry

JAPAN
KONICA Print Head



UV FLATBED SERIES

◀ **P-2513**

HAPOND UV FLATBED PRINTER

P-2513



TECHNICAL SPECIFICATIONS

Model	P-2513	
Dimension (LxWxH mm)	4780 x 2600 x 1500	
Weight (kg)	1200	
Max. Printing Width (mm)	2440 x 1220 (W x L)	
Ink Color	 Optional: 	
Ink Type	UV Curable Ink	
Print Head	KONICA 1024A, OPTIONAL: KONICA 1024i(6pl/13pl)	
No. Of Print Head	5 - 12 Units	
Printing Resolution (dpi)	480x1080, 480x1440, 540x1080, 540x1440	
Printing Speed (m ² /h)	4 Print Head	8 Print Head
Production Mode	28	42
Quality Mode	18	28
High Precision Mode	14	21
Printing Mode	Uni and Bi-Direction	
Media Type	Acrylic, Aluminum, Ceramic Tiles, Corrugated Board, Foam Board, Glass, Metal Plate, Back-Lit, Banner Flex, Canvas, Mesh Paper, Synthetic Paper, Reflective Film, Sticker, Tarpaulin, Textile, Non-Woven, Wall coverings, Soft Film, etc	
RIP & Control Software	Hapond Printer Manager, Photoprint, Optional: Caldera, Print Factory	
Curing System	LED UV System	
Cleaning System	Positive Flush	
Image Format	BMP, TIFF, JPEG, EPS, PDF, etc	
Color Management	ICC Profile	
Data Interface	USB 2.0/3.0	
Input Voltage	Single Phase, AC220V+/-10% (50/60Hz), 32A	
Working Environment	Temperature: 20°C - 28°C	Humidity: 40%-70% RH

Technical specification are subject to change without prior notice.

HAPOND
DIGITAL TECHNOLOGY SDN BHD

HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)



+603-4296 3733



+603-4296 9733



sales@hapond.com.my



hapond.com.my



facebook.com/haponddigital



21-23 Jalan Bukit Permai Utama 3,
Taman Industri Bukit Permai,
56100 Cheras, Kuala Lumpur

