

INSPIRING INNOVATION



MAIN APPLICATION

Decoration Industry

Advertising Industry

Interior Design Industry

Packaging Industry

Exhibition Industry

Leather & Textile Industry



PIEZOELECTRIC
NOZZLE



HIGH
RESOLUTION



DROP



VSD3



LAN CABLE



LONG LIFE



AUTOMATIC
CLEANING



STABLE
PRINTING



UV ROLL-TO-ROLL SERIES

 **IP1601/02 UI**

HAPOND UV ROLL-TO-TOLL PRINTER

IP1601/02 UI



TECHNICAL SPECIFICATIONS

Model	IP1801/02 UI			
Print Head	1~2 Unit EPSON i3200-U1			
Boards & RIP	Hoson Board & PhotoPrint UV RIP Software			
Ink	Hapond UV Ink			
Color Configuration				
Ink Supply System	Bulk ink Supply system with 1.5L Main INK tank			
Print Width	Max. 1800mm			
Media Type	Banner, Coated PP, Vinyl, PVC Film...			
Y-Axis	20mm Diameter			
Printing Bed	144mm Wide Printing Bed			
Suction System	Adjustable Vacuum Suction System			
Printing Speed	Mode	Resolution	1H	2H
	4PASS	720X1200	12m ² /h	24m ² /h
	6PASS	720X1800	8m ² /h	16m ² /h
	8PASS	720X2400	6m ² /h	12m ² /h
Heating System	Rear-Printing Bed-Front 3 Heater			
Drying System	LED Curing System			
Printer Size	2785*670*1300 mm (L*W*H)			
Printer Packing	Wooden Box			
N.W/G.W.	202KG / 295KG			
Packing size	3400*570*650 mm (L*W*H)			
Input Voltage	AC220 50/60Hz			
Working Enviroment	Temperature: 20-28°C, Humidity: 25-65%			

Technical specifications are subject to change without prior notice.

HAPOND
DIGITAL TECHNOLOGY SDN BHD

HAPOND DIGITAL TECHNOLOGY SDN. BHD. (788546-V)

+603-4296 3733

sales@hapond.com.my

facebook.com/haponddigital

+603-4296 9733

hapond.com.my

21-23 Jalan Bukit Permai Utama 3,
Taman Industri Bukit Permai,
56100 Cheras, Kuala Lumpur

